

Created By: FSW IMC4500

Your Configured Ricoh IM C4500



*Note: The image is a photo realistic illustration of your selected configuration.

DIMENSIONS

WIDTH	DEPTH	HEIGHT
23.10in	27.00in	42.60in
(587mm)	(686mm)	(1,082mm)

Actual dimensions may vary. These are approximate only.

POWER CONSUMPTION (MAIN UNIT)

120V-127V, 60Hz

Additional power requirements may apply.

Please read each option's description copy to see if additional power sources are needed.

Your Chosen Options

- IM C4500
- Paper Feed Unit PB3270
- Caster Table Type M3
- Internal Finisher SR3250
- PostScript3 Unit Type M37
- Fax Option Type M37
- ESP XG-PCS-15D



Main Unit

Main Unit		
Item/Description	Item #	Power Requirements
IM C4500	418227	120V-127V, 60Hz

Paper Tray & Optional Accessories		
Item/Description	Item #	Power Requirements
Paper Feed Unit PB3270	418355	N/A
Caster Table Type M3	416737	N/A

Output & Finishing Options

Internal		
Item/Description	Item #	Power Requirements
Internal Finisher SR3250	418378	N/A

Print/Scan Options

Network Environment		
Item/Description	Item #	Power Requirements
PostScript3 Unit Type M37	418406	N/A

Fax Options		
Item/Description	Item #	Power Requirements
Fax Option Type M37	418600	N/A

Security & Miscellaneous Accessories		
Item/Description	Item #	Power Requirements
ESP XG-PCS-15D	006428MIU	N/A



Main Unit Main Unit Thumbnail Item/Description Item # 418227 **IM C4500** • Output Speed (Letter): 45-ppm • Average Monthly Volume: 10,000 impressions/month • Maximum Monthly Volume: 50,000 impressions/month • Power Requirements: 120V-127V, 60Hz • Weight: 223.5 lbs. (101.4 kg) • W × D × H (inches): $23.1 \times 27 \times 37.9$ • W × D × H (mm): 586.74 × 685.8 × 962.66 Note: The DOSS does not overwrite the HDD for the Color Controller E-25C.

Paper Tray & Optional Accessories		
Item/Description	Item #	Thumbnail
Paper Feed Unit PB3270	418355	
Recommended paper feed unit for environments that prefer their system at the lowest height possible, making it easier for all users to access the device (Section 508).		
Provides an additional 550 sheets.		
Paper sizes up to 12" x 18".		
Paper weights up to 80 lb. Bond/166 lb. Index (300g/m ²).		
Weight: 24 lbs. (13 kg)		
$W \times D \times H$ (inches): 23.1 × 27 × 4.7		
W × D × H (mm): 586.74 × 685.8 × 119.38		
Note: 1. By choosing this option, Caster Table Type M3 will be added to your configuration. 2. Paper Feed Unit PB3270 cannot be installed with Paper Feed Unit PB3280, Paper Feed LCIT PB3290, LCIT RT3040, Cabinet Type F, Finisher SR3260, Finisher SR3280, Booklet Finisher SR3270, Booklet Finisher SR3290 or any related options.		

Caster Table Type M3	416737	H -	" A
The caster table must be added to the configuration when the Paper Feed Unit			
PB3270 is selected. It provides a platform with wheels to easily move the device.			
Note:			
1. By choosing this option, Paper Feed Unit PB3270 will be added to your configuration.			
2. Caster Table Type M3 cannot be installed with Paper Feed Unit PB3280, Paper Feed LCIT			
PB3290, LCIT RT3040, Cabinet Type F, Finisher SR3260, Finisher SR3280, Booklet Finisher			
SR3270, Booklet Finisher SR3290 or any related options.			

Output & Finishing Options

Internal Finisher SR3250 500-sheet Internal Finisher provides multi-position stapling and optional hole punching. Recommended for offices with limited floor space. Supports paper sizes up to 12" x 18". Weight: 28.2 lbs. (12.8 kg) W × D × H (inches): 21.5 × 20.6 × 6.7 W × D × H (mm): 546.1 × 523.24 × 170.18 Note: Internal Finisher SR3250 cannot be installed with IM C6000, Internal Shift Tray SH3080, Internal

Multi-Fold Unit, Finisher SR3260 Finisher SR3280, Booklet Finisher SR3270, Booklet Finisher

Print/Scan Options

SR3290 or any related options.

Network Environment

Item/Description	Item #	Thumbnail
PostScript3 Unit Type M37 Genuine Adobe® PostScript®3™. Recommended for printing more complex color and PDF files. The IM C4500 and IM C6000 come with standard PostScript3 and PDF Direct Print Emulation. This option is available for customers who require True Adobe® workflows like Photoshop®, Illustrator® and PDF/X as well as additional font support. When enabled on the MFP, the standard PostScript3 Emulation will be disabled. Note: Postscript3 Unit Type M37 cannot be installed with Color Controller E-25C or any related options.	418406	Adobe PostScript 3 Optional

Fax Options		
Item/Description	Item #	Thumbnail
Fax Option Type M37	418600	Fax Destination
Installation required to enable fax services: 33.6 kbps, approximately 2 second transmission speed, standard JBIG, and standard 320 Pages Memory. Includes		Enter fax destination with the Numb
ndard Internet Fax (T.37), LAN Fax, IP-Fax (T.38), Fax Forwarding to Email & perless Fax function.		▶ Destination 912015551234_ Tone Pause

Security & Miscellaneous Accessories		
Item/Description	Item #	Thumbnail
ESP XG-PCS-15D Designed to provide a higher level of noise filtering and surge protection for devices that employ more sensitive and complex electronic components. Our Advanced Technical Support (ATS) recommends the use of power protection products to minimize potential electrical interference with products.	006428MIU	

Ricoh is committed to creating value for our customers through the production of top quality products, services and solutions that directly meet the needs of today's communication intensive business environments. As a result, we offer a range of Multifunction products with advanced scanning and printing software options that help boost productivity and improve workflow by enhancing the user experience. Visit Ricoh-USA.com for more information.

We offer a variety of services and solutions to meet diverse and challenging business needs. To find out more information, visit solutions ricoh-usa.com

The content on this site, and the appearance, features and specifications of Ricoh products and services are subject to change from time to time without notice. Products are shown with optional features. While care has been taken to ensure the accuracy of this information, Ricoh makes no representation or warranties about the accuracy, completeness or adequacy of the information contained herein, and shall not be liable for any errors or omissions in these materials. Actual results will vary depending upon use of the products and services, and the conditions and factors affecting performance. The only warranties for Ricoh products and services are as set forth in the express warranty statements accompanying them.

Ricoh USA, Inc., 300 Eagleview Boulevard, Exton, PA 19341, 1-800-63-RICOH. ©2020 Ricoh USA, Inc. All rights reserved. Ricoh® and the Ricoh Logo are registered trademarks of Ricoh Company, Ltd. All other trademarks are the property of their respective owners.

